

IN THE CLAIMS:

The text of all pending claims, (including withdrawn claims) is set forth below. Cancelled and not entered claims are indicated with claim number and status only. The claims as listed below show added text with underlining and deleted text with ~~strikethrough~~. The status of each claim is indicated with one of (original), (currently amended), (cancelled), (withdrawn), (new), (previously presented), or (not entered).

Please AMEND claim 1 in accordance with the following:

1. (CURRENTLY AMENDED) A gas-discharge tube, comprising a tubular body in which a discharge gas is sealed and a plurality of electrodes, for discharging said discharge gas by applying a voltage to each of said plurality of electrodes, wherein

a recess portion is formed on an external surface of said tubular body, and
said plurality of electrodes include a plurality of pairs of sustain electrodes for displaying and an address electrode for selectively displaying said pairs of sustain electrodes.

said plurality of pairs of sustain electrodes are formed on the external surface of said tubular body at a position opposite to said recess portion, and

~~an entirety of at least one said address electrode among said plurality of electrodes is placed thoroughly inside of said recess portion.~~

2. (ORIGINAL) The gas-discharge tube as set forth in Claim 1, wherein
an inner surface of a region of said tubular body, where electrodes not being placed in said recess portion among said plurality of electrodes are placed, is formed to have a microscopic unevenness, and

a secondary electron emission film is provided at a portion where said microscopic unevenness is formed.

3. (ORIGINAL) The gas-discharge tube as set forth in Claim 1, wherein
electrodes not being placed in said recess portion among said plurality of electrodes are placed on an external surface of the side opposed to said recess portion of said tubular body,

the inner surface of the portion of said tubular body, where said recess portion is formed, is formed to have a protrusion portion toward the inside, and

a member on which phosphor is arranged is placed at the inner surface of said

portion of said tubular body where said protrusion portion is formed toward the inside.

4. (ORIGINAL) The gas-discharge tube as set forth in Claim 3, wherein
an inner surface of a region of said tubular body, where electrodes not being
placed in said recess portion among said plurality of electrodes are placed, is formed to have a
microscopic unevenness, and
a secondary electron emission film is provided at a portion where said
microscopic unevenness is formed.

5. (ORIGINAL) The gas-discharge tube as set forth in Claim 1, wherein said recess
portion is a trench extending in the axial direction of said tubular body.

6. (ORIGINAL) The gas-discharge tube as set forth in Claim 5, wherein
an inner surface of a region of said tubular body, where electrodes not being
placed in said recess portion among said plurality of electrodes are placed, is formed to have a
microscopic unevenness, and
a secondary electron emission film is provided at a portion where said
microscopic unevenness is formed.

7. (ORIGINAL) The gas-discharge tube as set forth in Claim 2, wherein
electrodes not being placed in said recess portion among said plurality of
electrodes are placed on an external surface of the side opposed to said recess portion of said
tubular body,
the inner surface of the portion of said tubular body, where said recess portion is
formed, is formed to have a protrusion portion toward the inside, and
a member on which phosphor is arranged is placed at the inner surface of said
portion of said tubular body where said protrusion portion is formed toward the inside.

8. (ORIGINAL) The gas-discharge tube as set forth in Claim 7, wherein
an inner surface of a region of said tubular body, where electrodes not being
placed in said recess portion among said plurality of electrodes are placed, is formed to have a
microscopic unevenness, and
a secondary electron emission film is provided at a portion where said
microscopic unevenness is formed.

9. (WITHDRAWN) A gas-discharge tube, comprising a tubular body in which a discharge gas is sealed and a plurality of electrodes, for discharging said discharge gas by applying a voltage to each of said plurality of electrodes, wherein

an inner surface of said tubular body is formed to have a microscopic unevenness, and

a secondary electron emission film is provided at a portion where said microscopic unevenness is formed.

10. (WITHDRAWN) The gas-discharge tube as set forth in Claim 9, wherein said microscopic unevenness is formed in the axial direction of said tubular body.

11. (WITHDRAWN) The gas-discharge tube as set forth in Claim 9, wherein said electrodes include a first electrode placed in the axial direction of said tubular body, and a plurality of second electrodes opposed to said first electrode via said tubular body and being placed at predetermined intervals parallel to the direction crossing the axial direction of said tubular body, and

said microscopic unevenness is formed at a region where said plurality of second electrodes is placed.

12. (WITHDRAWN) The gas-discharge tube as set forth in Claim 11, wherein said microscopic unevenness is formed in the axial direction of said tubular body.

13. (WITHDRAWN) A gas-discharge tube, comprising a tubular body in which a discharge gas is sealed and a plurality of electrodes, for discharging said discharge gas by applying a voltage to each of said plurality of electrodes, wherein

an external surface of the region of said tubular body, where at least one electrode among said plurality of electrodes is placed, is formed in a plane shape,

the inner periphery of the cross-section across the axis of said tubular body is formed in a circular shape, and

a secondary electron emission film is provided at an inner surface of said tubular body.

14. (ORIGINAL) A display apparatus in which a plurality of gas-discharge tubes are

arranged parallel to each other, each gas-discharge tube comprising: a tubular body in which a discharge gas is sealed; a first electrode placed in the axial direction of said tubular body; and a plurality of second electrodes opposed to said first electrode via said tubular body and being placed at predetermined intervals parallel to the direction crossing the axial direction of said tubular body, so that said discharge gas is discharged by applying a voltage to each electrode, and said second electrodes of adjacent gas-discharge tubes being electrically connected to each other, wherein

a recess portion is formed on an external surface of said tubular body,
said first electrode is placed in said recess portion of said tubular body,
the inner surface of the portion of said tubular body, where said recess portion is formed, is formed to have a protrusion portion toward the inside, and
a member on which phosphor is arranged is placed at the inner surface of the portion where said protrusion is formed toward the inside of said tubular body.

15. (ORIGINAL) The display apparatus as set forth in Claim 14, wherein
the inner surface of a region of each of said tubular body, where said second electrodes are placed, is formed to have a microscopic unevenness, and
a secondary electron emission film is provided at a portion of said inner surface where said microscopic unevenness is formed.